

## SAFETY LASER 3000 SW 7012



RX

- 12V/24V dc POSITIVE +
- 12V/24V dc NEGATIVE -
- COMMON
- N.O. relay contact

TX

- 12V/24V dc POSITIVE +
- 12V/24V dc NEGATIVE -

distance/ distancia/ distanza / Distanz  
10 m MAX

use cables 0,5mm<sup>2</sup>

## SAFETY SOLAR 3001 SW 7112 (solar)



RX

- 12V/24V dc POSITIVE +
- 12V/24V dc NEGATIVE -
- COMMON
- N.O. (do not connection, non collegare, no conecte,  
ne pas connecter, anschliessen Sie nicht)



TX

- 12V/24V dc POSITIVE +
- 12V/24V dc NEGATIVE -

distance/ distancia/ distanza / Distanz  
10 m MAX

use cables 0,5mm<sup>2</sup>

CE conformity declaration:

we declare that the product:SW7012 and SW7112  
is in compliance with CE norms EN 61000-6-1/3

89/336/EEC

July 2008

Allducks srl A.D. A.Toutberidze



CE  
RoHS

Allducks srl

via Alessandro Volta, 1  
20060 Ornago (MI) Italy

Tel. +39/039/6010654

Fax +39/039/6011243

info@allducks.it www.allducks.it